

BALMASTER BESTFLEX 4SP



DIN EN 856 4SP / ISO 3862 - 10.1008.-F

Very high pressure, extra flexible, four steel wire spirals reinforced hydraulic hose

REFERENCE	#	inch	inch	SAE Dash	ID	OD	MPa		MIN BEND RAD		KG	
					mm	mm	MPa	PSI	MPa	PSI	mm	kg/m
4SP-04-F	10.1008.04F	DN6	1/4"	-4	6.5	17,4	45,0	6600	180,0	26400	150	0,70
4SP-06-F	10.1008.06F	DN10	3/8"	-6	9.6	19,9	44,5	6500	178,0	26000	180	0,80
4SP-08-F	10.1008.08F	DN12	1/2"	-8	12,9	22,8	41,5	6100	166,0	24400	230	1,15
4SP-10-F	10.1008.10F	DN16	5/8"	-10	16.0	26,4	42,0	6000	168,0	24000	250	1,26
4SP-12-F	10.1008.12F	DN19	3/4"	-12	19.2	30,6	38,0	5600	152,0	22400	300	1,44
4SP-16-F	10.1008.16F	DN25	1"	-16	25,6	37,7	32,0	4700	128,0	18800	340	2,15
4SP-20-F	10.1008.20F	DN31	1.1/4"	-20	32.1	48,6	21,0	3100	84,0	12400	460	2,75
4SP-24-F	10.1008.24F	DN38	1.1/2"	-24	38.3	55,0	21,0	3100	84,0	12400	560	3,35
4SP-32-F	10.1008.32F	DN51	2"	-32	51.0	68,1	17,5	2600	70,0	10400	660	4,60

INNER TUBE: seamless oil resistant synthetic rubber
REINFORCEMENT: 4 spirals of high tensile steel wire
OUTER TUBE: black wrapped, oil, weather and abrasion resistant synthetic rubber
SAFETY FACTOR: 4:1

APPLICATION: petroleum base hydraulic fluids
TEMPERATURE RANGE: -40°C (-40°F) +100°C (+212°F); Intermittent service: +120°C (+248°F) Max. temperature recommended for water base hydraulic fluids: +70°C (+158°F) Max. temperature recommended for air: +60°C (+140°F)

COUPLINGS: Balflex® 2-piece fittings serie 23/24 with 20 serie ferrules, Balflex® Multicrimp fittings serie BW23
 *On sizes - 6 (3/8") and - 8 (1/2") the Balflex® BALMASTER DIN EN 856 4SP and Balflex® POWERSPIR SAE 100R15 hoses are the same, and they are branded Balflex® POWERSPIR.

AVAILABLE VERSIONS: tough cover / Armourguard

BALFLEX /// **BALMASTER BESTFLEX** DIN EN 856 - 4SP - DN6 - 1/4" - ISO 3862 - WP ^{45 MPa} 6600 PSI - Flame Resistant - MSHA IC-252/00